

The aluminium radicle replies copper plate performance table

Performance beacon

Item	Test a condition	AL-01-P Specification	AL-01-A Specification	AL-01-B Specification	AL-01-L Specification	Unit
Thermal conductivity	A	0.6-0.8	1.0-1.8	2.0-2.8	3.0	W/m.K
Thermal re – sistance		≤ 0.78	≤0.64	≤0.45	≤0.2	°C/W
Solder resistance	288deg.c	120	120	120	120	Sec.
Peel strength normal status	A Thermal stress post	1.4 1.4	1.5 1.5	1.5 1.5	1.3 1.3	N/mm
Volume resistivity normal status	C-96/35/90 E-24/125	10 ⁸ 10 ⁶	10 ⁸ 10 ⁶	10 ⁸ 10 ⁶	10 ⁸ 10 ⁶	MΩ.CM
Surface resistivity normal status	C-96/35/90 E-24/125	10 ⁷ 10 ⁶	10 ⁷ 10 ⁶	10 ⁷ 10 ⁶	10 ⁷ 10 ⁶	MΩ
Dielectric constant	C-96/35/90	4.2	4.9	4.9	4.9	1MH2
Dissipation Factor	C-96/35/90	≤0.02	≤0.02	≤0.02	≤0.02	1MH2
Water absorption		0.1	0.1	0.1	0.1	%
BreakdownVoltage	D-48/50+D-0.5/23	3	3	3	3	KV
Insulationstrength	A	30	30	50	30	KV/mm
Raise camber	A	0.5	0.5	0.5	0.5	%
Flameability	UL94	V-0	V-0	V-0	V-0	
CTI	IEC60112	600	480	480	480	V
TG		158	130	130	130	°C

Product thickness mm	The actinium screen is thick: 1 oz ~ 15 oz, The aluminium board is thick: 0.6 ~ 5.0 mm (Tolerance range ±0.10mm)	
Product specification mm	500×600	500×1200

- The power is hybrid IC(HIC)
- Voice frequency equipment:input, output amplifier, compensating capacitor, the voice frequency amplifier, preamplifier, power amplifier etc..
- Power supply equipment:series voltage regulation, switch modulator, and DC-AC transducer...etc..
- Telecommunication electron equipment:high frequency amplifier, filter telephone, send a telegram telephone.
- Office automation:the printer driver, big electronic display substrate and thermal print A class.
- Autocar:the igniter, power supply modulator and swap transform machine, power supply controller, become only system etc..
- Calculator:CPU board, soft pan driver, and power supply device...etc..
- Power mold mass:change to flow a machine, solid relay, commutate bridge etc..
- LED light, heat and water expense:big power LED light, LED wall etc..

The Bo Yu science and technology limited company

Water orifice in Hui state City in Guangdong, China province
water orifice in the town big pass the No.27 first floor turnkey
plant
TEL:0752-2319005 FAX : 0752-2319007
Email: hzsby2009@163.com

The aluminium radicle replies copper plate performance table

Performance beacon

Item	Test a condition	Unit	CU-01-P Specification	CU-01-B Specification
Thermal conductivity	A	W/m.K	0.6-0.8	2.0-2.8
Thermal re - sistance		°C/W	≤ 0.78	≤0.45
Solder resistance	288°C	Sec.	120	120
Peel strength normal status	A Thermal stress post	N/mm	1.4 1.4	1.5 1.5
Volume resistivity normal status	C-96/35/90 E-24/125	MΩ.CM	10 ⁸ 10 ⁶	10 ⁸ 10 ⁶
Surface resistivity normal status	C-96/35/90 E-24/125	MΩ	10 ⁷ 10 ⁶	10 ⁷ 10 ⁶
Dielectric constant	C-96/35/90	1MH2	4.2	4.9
Dissipation Factor	C-96/35/90	1MH2	≤0.02	≤0.02
Water absorption		%	0.1	0.1
BreakdownVoltage	D-48/50+D-0.5/23	KV	3	3
Insulationstrength	A	KV/mm	30	30
Raise camber	A	%	0.5	0.5
Flameability	UL94		V-0	V-0
CTI	IEC60112	V	600	480
TG		°C	158	130

Product thickness mm	600*500
Product specification mm	The actinium screen is thick: : H oz ~ 15 oz, The aluminium board is thick: : 0.8 ~ 5.0 mm (Tolerance range ±0.10mm)

- The power is hybrid IC(HIC)
- Voice frequency equipment:input, output amplifier, compensating capacitor, the voice frequency amplifier, preamplifier, power amplifier etc..
- Power supply equipment:series voltage regulation, switch modulator, and DC-AC transducer...etc..
- Telecommunication electron equipment:high frequency amplifier, filter telephone, send a telegram telephone.
- Office automation:the printer driver, big electronic display substrate and thermal print A class.
- Autocar:the igniter, power supply modulator and swap transform machine, power supply controller, become only system etc..
- Calculator:CPU board, soft pan driver, and power supply device...etc..
- Power mold mass:change to flow a machine, solid relay, commutate bridge etc..
- LED light, heat and water expense:big power LED light, LED wall etc..

The Bo Yu science and technology limited company

Water orifice in Hui state City in Guangdong, China province
water orifice in the town big pass the No.27 first floor turnkey
plant
TEL:0752-2319005 FAX : 0752-2319007
Email: hzsby2009@163.com